

SHIBAURA

COMPACT TRACTOR

ST318

ST321

ST324

ST329

ST333



SHIBAURA SOMETHING

SHIBAURA COMPACT DIESEL ENGINE -THE ONE YOU CAN TRUST

Environment-Friendly

The Shibaura diesel engine mounted on the ST-series tractor is surely environment-friendly. It meets the US EPA Tire-1 which is recognized as one of the toughest emission criteria in the world at present. Besides, the engine design takes the EU DGXI Stage 2 emission regulation into account.

In order to satisfy upcoming emission control regulations, Shibaura will design its diesel engine to achieve better combustion efficiency, emission and less fuel consumption.

Low Noise and Low Vibration

The Shibaura diesel engine realizes low noise and low vibration in the whole engine revolution range.

The engine has proper rigidity of the cylinder block and gear case cover, which helps reducing its mechanical and combustion noise.



Compact and Light-Weight

Applying Finite Element Method(FEM)for structural analysis, Shibaura designs its diesel engine to be compact and light-weight on the basis of the appropriate balance of rigidity, strength, and weight.

Easy Maintenance

The Shibaura diesel engine is ideal when it comes to easy maintenance.

On one side of the engine, you can check the oil level, replace the oil filter and complete some other necessary maintenance.

ELEGANT & SLEEK APPEARANCE

- ✓ Beautiful round shape body with Shibaura red color

EASY & PLEASANT OPERATION

- ✓ Simple but well organized instrument panel
- ✓ Levers neatly located on fenders
- ✓ Horizontal moving acceleration lever
- ✓ Push/Pull 2WD/4WD switch lever
- ✓ Power assisted steering
- ✓ Hydraulic Transmission (for HST Model only)
- ✓ Electronic cruise control (for HST Model only)



ULTIMATE SAFETY

- ✓ Safety lock feature ensuring you to get the engine started only with the PTO & SPEED lever in neutral
- ✓ Two post foldable ROPS

CLEAR VIEW FROM OPERATORS SEAT

- ✓ No obstruction ahead from operators position with the muffler located inside the bonnet.

SHIBAURA BRAND-NEW ST SERIES IMPRESSING YOU CAN NOT LEAVE BEHIND

Being substituted for the long-seller
Shibaura S-series compact tractors,
the brand-new value conscious ST series
is now arriving at field,
impressing you with the sophisticated design
and state-of-the-art technology.



POWERFUL & VERSATILE PERFORMANCE

- ✓ Four Wheel Drive
- ✓ Efficient Diesel Engine
- ✓ Category 1 three point hitch
- ✓ Single/Double acting remote valve (Option)
- ✓ Hydraulic outlet on the right hand side of the tractor
- ✓ Mid/Rear PTO (Option)
- ✓ Mid-Mount rotary mower (48/60 inch side discharge as option)



Mid-Mount Rotary Mower

RIES BEHIND



ST318
18.5hp (13.8kW)
MECH/HST



ST321
21.0hp (15.7kW)
MECH/HST



ST324
24.0hp (17.9kW)
MECH/HST



ST329
29.0hp (21.6kW)
MECH/HST



ST333
33.0hp (24.6kW)
MECH/HST



EXCELENT ACCESSABILITY & MAINTENANCIBILITY

- ✓ Flip up bonnet & side guard
- ✓ Easy radiator screen removal
- ✓ Dual air cleaner elements

SPECIFICATIONS

TRACTOR MODEL		ST318		ST321		ST324	
Drive		4WD		4WD		4WD	
Transmission type		MECH	HST	MECH	HST	MECH	HST
Engine (Diesel)							
Model		S753		S773		S773L	
Engine gross power * 1	hp (kW)	18.5 (13.8)		21 (15.7)		24 (17.9)	
No. of cylinders		3		3		3	
Total displacement	cc (cu.in.)	954 (58.2)		1,005 (61.3)		1,131 (69.0)	
Rated speed	rpm	2,600		2,600		2,600	
Battery	V-A	12-36		12-36		12-36	
Alternator	A	40		40		40	
Fuel tank capacity	litre (US gal.)	20 (5.3)		20 (5.3)		20 (5.3)	
PTO							
Type		Trans.w/ one way clutch	Live	Trans.w/ one way clutch	Live	Trans.w/ one way clutch	Live
Rear PTO power * 1	hp (kW)	15 (11.2)	14 (10.4)	17 (12.7)	16 (11.9)	19 (14.1)	18 (13.4)
Rear PTO rated speed (@ 2,600rpm Engine Rated Speed)	rpm	588	561	588	561	588	561
Mid PTO rated speed (@ 2,600rpm Engine Rated Speed)	rpm	Opt. (2,139)	2,040	Opt. (2,139)	2,040	Opt. (2,139)	2,040
Hydraulic							
Lift control type: Position		Standard		Standard		Standard	
Max. Lifting Capacity	kg (lb.)	669 (1,474)		669 (1,474)		669 (1,474)	
Draft		NA		NA		NA	
3-point hitch, Category - 1	Fixed Drawbar	Standard		Standard		Standard	
Traveling System							
Steering		Power Steering		Power Steering		Power Steering	
Brake		Wet Disk		Wet Disk		Wet Disk	
Clutch		Dry, Single		Dry, Single		Dry, Single	
Standard Tire Size							
Agricultural	Front	5-12		6-12		6-12	
	Rear	8-16		9.5-16		9.5-16	
Turf	Front	20×8.00-10		20×8.00-10		20×8.00-10	
	Rear	29×12.00-15		29×12.00-15		29×12.00-15	
Traveling Speed-Speed Range (at rated engine speed)							
Forward		9	High & Low (2-range)	9	High & Low (2-range)	9	High & Low (2-range)
First	km/h (mph)	1.08 (0.67)	0~5.78 (0~3.61)	1.15 (0.72)	0~5.78 (0~3.61)	1.13 (0.71)	0~5.78 (0~3.61)
Second	km/h (mph)	1.79 (1.12)	0~14.86 (0~9.29)	1.91 (1.19)	0~14.86 (0~9.29)	1.89 (1.17)	0~14.86 (0~9.29)
Third	km/h (mph)	2.40 (1.50)	—	2.56 (1.60)	—	2.53 (1.57)	—
Fourth	km/h (mph)	2.57 (1.61)	—	2.74 (1.71)	—	2.85 (1.77)	—
Fifth	km/h (mph)	4.26 (2.67)	—	4.54 (2.84)	—	4.74 (2.94)	—
Sixth	km/h (mph)	5.72 (3.58)	—	6.10 (3.81)	—	6.36 (3.95)	—
Seventh	km/h (mph)	6.72 (4.20)	—	7.16 (4.48)	—	7.16 (4.48)	—
Eighth	km/h (mph)	11.15 (6.97)	—	11.89 (7.43)	—	11.89 (7.43)	—
Ninth	km/h (mph)	14.96 (9.35)	—	15.95 (9.97)	—	15.95 (9.97)	—
Reverse		3	High & Low (2-range)	3	High & Low (2-range)	3	High & Low (2-range)
First	km/h (mph)	1.99 (1.23)	0~3.85 (0~2.40)	2.13 (1.33)	0~4.08 (0~2.55)	2.11 (1.31)	0~4.08 (0~2.55)
Second	km/h (mph)	4.77 (2.98)	0~9.91 (0~6.19)	5.08 (3.18)	0~10.50 (0~6.56)	5.30 (3.29)	0~10.50 (0~6.56)
Third	km/h (mph)	12.47 (7.79)	—	13.29 (8.25)	—	13.29 (8.25)	—
Dimensions							
Overall length (w/3P)		mm (in.)	2,728 (107.4)	2,728 (107.4)		2,728 (107.4)	
Overall width (Std. tread, w/Ag. tires)		mm (in.)	1,042 (41.0)	1,138 (44.8)		1,138 (44.8)	
Overall height (w/Ag. tires & ROPS)		mm (in.)	2,262 (89.1)	2,287 (90.0)		2,287 (90.0)	
Wheelbase		mm (in.)	1,405 (55.3)	1,405 (55.3)		1,405 (55.3)	
Min. ground clearance (w/Ag. tires, Drawbar)		mm (in.)	245 (9.6)	270 (10.6)		270 (10.6)	
Tread	Front (w/Ag. tires, Std.)	mm (in.)	822 (32.4)	848 (33.4)		848 (33.4)	
	Rear (w/Ag. tires, Std.)	mm (in.)	851 (33.5)	897 (35.3)		897 (35.3)	
Weight (w/Ag. tires & ROPS)		kg (lb.)	742 (1,636)	754 (1,662)	744 (1,640)	756 (1,666)	750 (1,653) 762 (1,680)

*1 Manufacturer's estimation

The above specifications are subject to change without notice

SPECIFICATIONS

TRACTOR MODEL		ST329		ST333	
Drive		4WD		4WD	
Transmission type		MECH	HST	MECH	HST
Engine (Diesel)					
Model		J843		N843	
Engine gross power * 1	hp (kW)	29.0 (21.6)		33.0 (24.6)	
No. of cylinders		3		3	
Total displacement	cc (cu.in.)	1,330 (81.2)		1,496 (91.3)	
Rated speed	rpm	2,800		2,800	
Battery	V - A	12 - 55		12 - 55	
Alternator	A	40		40	
Fuel tank capacity	litre (US gal.)	30 (7.9)		30 (7.9)	
PTO					
Type		Trans.w/one way clutch	Live	Trans.w/one way clutch	Live
Rear PTO power * 1	hp (kW)	25.1 (18.7)	23.6 (17.6)	28.8 (21.3)	26.9 (20.1)
Rear PTO rated speed (@ 2,800rpm Engine Rated Speed)	rpm	625	613	625	613
Mid PTO rated speed (@ 2,800rpm Engine Rated Speed)	rpm	Opt. (2,356)	2,314	Opt. (2,356)	2,314
Hydraulic					
Lift control type: Position		Standard		Standard	
Max. Lifting Capacity	kg (lb.)	873 (1921)		873 (1921)	
Draft		Option		Option	
3-point hitch, Category - 1	Swinging Drawbar	Standard		Standard	
Traveling System					
Steering		Power Steering		Power Steering	
Brake		Wet Disk		Wet Disk	
Clutch		Dry, Single		Dry, Single	
Standard Tire Size					
Agricultural	Front	6-14		7-14	
	Rear	9.5-24		11.2-24	
Turf	Front	25×8.50-14		25×8.50-14	
	Rear	13.6-16		13.6-16	
Traveling Speed - Speed Range (at rated engine speed)					
Forward		9	High/Middle/Low (3-range)	9	High/Middle/Low (3-range)
First	km/h (mph)	1.25 (0.78)	0 ~ 5.34 (0 ~ 3.32)	1.30 (0.81)	0 ~ 5.59 (0 ~ 3.48)
Second	km/h (mph)	1.84 (1.15)	0 ~ 12.48 (0 ~ 7.76)	1.94 (1.20)	0 ~ 13.07 (0 ~ 8.13)
Third	km/h (mph)	2.65 (1.65)	0 ~ 24.04 (0 ~ 14.94)	2.78 (1.72)	0 ~ 25.18 (0 ~ 15.65)
Fourth	km/h (mph)	3.95 (2.45)	—	4.14 (2.58)	—
Fifth	km/h (mph)	5.83 (3.62)	—	6.11 (3.80)	—
Sixth	km/h (mph)	8.39 (5.21)	—	8.78 (5.44)	—
Seventh	km/h (mph)	10.11 (6.28)	—	10.58 (6.58)	—
Eighth	km/h (mph)	14.93 (9.28)	—	15.65 (9.72)	—
Ninth	km/h (mph)	22.00 (13.67)	—	23.04 (14.32)	—
Reverse		3	High/Middle/Low (3-range)	3	High/Middle/Low (3-range)
First	km/h (mph)	1.84 (1.15)	0 ~ 3.74 (0 ~ 2.32)	1.94 (1.20)	0 ~ 3.92 (0 ~ 2.48)
Second	km/h (mph)	5.83 (3.62)	0 ~ 8.74 (0 ~ 5.44)	6.11 (3.80)	0 ~ 9.15 (0 ~ 5.70)
Third	km/h (mph)	14.93 (9.28)	0 ~ 16.82 (0 ~ 10.46)	15.65 (9.72)	0 ~ 17.63 (0 ~ 10.96)
Dimensions					
Overall length (w/3P)		2830 (111.4)		2830 (111.4)	
Overall width (Std. tread, w/ Ag. tires)		1400 (55.1)		1400 (55.1)	
Overall height (w/ Ag. tires & ROPS)		2460 (96.9)		2460 (96.9)	
Wheelbase		1600 (63.0)		1600 (63.0)	
Min. ground clearance (w/ Ag. tires, Drawbar)		285 (11.2)		300 (11.8)	
Tread	Front (w/ Ag. tires, Std.)	1100 (43.3)		1100 (43.3)	
	Rear (w/ Ag. tires, Std.)	1115 (43.9)		1115 (43.9)	
Weight (w/ Ag. tires & ROPS)		1085 (2392)	1075 (2370)	1100 (2425)	1090 (2403)

*1 Manufacturer's estimation

Specifications subject to change without notice



SHIBAURA

Ishikawajima-Shibaura Machinery Co., Ltd.

Head Office : HERMONY TOWER,